

Queries

Cutoffs management

1. Each saleshead should have an equivalent number of transactioncutoffs table

```
set @terminalno = 1;
```

```
select count(*)  
from saleshead  
where terminalno = @terminalno;
```

```
select count(*)  
from transactioncutoffs as T, saleshead as H  
where H.wid = T.salesheadwid  
and H.terminalno = @terminalno;
```

2. Re-initialize the transactioncutoffs table if found out that it doesn't tally with the saleshead count OR the 00:00:00 cutoff id is not 1.

```
truncate table transactioncutoffs;  
insert into transactioncutoffs (salesheadwid,cutoffid)  
select wid, 1 from saleshead;
```

3. Fix discrepancies in the transactioncutoffs table

A. check if there are duplicates

```
select count(*), cutoffid from transactioncutoffs group by cutoffid;
```

B. fix the duplicate entries by running this

```
drop table transactioncutoffs;  
  
update `cutoffs` set id='1' where cutofftime = '00:00:00';
```

C. Run the POS for it to recreate the transactioncutoffs table.

4. set the effective date for the 00:00:00 cutofftime to the year 2000

```
update cutoffs set effectivedate = '2000-01-01' where cutofftime = '00:00:00';
```

Queries

Unique solution ID: #1120

Author: Robi Navarro

Last update: 2019-01-18 08:39